



TECHNICAL DATA SHEET



Clinox ECO X2

Clinox PRO X2

Clinox AIR X2

Clinox POWER X2

Clinox SURFACE X2

TDS_X2LINE_2022_04*PRO

Mains Voltage	230 V - 50/60Hz	230 V - 50/60 Hz	230 V - 50/60 Hz	230 V - 50/60 Hz	230 V - 50/60 Hz
Maximum primary power	1200 VA	1800VA	1200VA	1800VA	2400VA
Output current	0 - 30 A	0 - 30 A	0 - 30 A	0 - 30 A	0 - 30 A
Output voltage	3 - 30 V AC/DC	3 - 30 V AC/DC	3 - 30 V AC/DC	3 - 30 V AC/DC	3 - 30 V AC/DC
Output power	900 W	900 W	900 W	1500 W	2400 W
Voltage regulation	3-30V (step 1V)	3-30V (step 1V)	3-30V (step 1V)	3-30V (step 1V)	3-30V (step 1V)
Current regulation	1 fixed position: 30 A	2 Positions: Low: 15 A High: 30 A	2 Positions: Low: 15 A High: 30 A	3 Positions: Low: 15 A Mid: 30 A High: 50 A	3 Positions: Low: 30 A Mid: 50 A High: 100 A
Tank capacity	-	1,8 l	1,8 l	1,8 l	1,8 l
Dispensig rate	-	1-3,6 l/h	1-3,6 l/h	1-3,6 l/h	1-3,6 l/h
Pump regulation	-	Dynamic Manual	Dynamic Manual	Dynamic Manual	Dynamic Manual
	-	Automatic: 8 levels	Automatic: 8 levels	Automatic: 8 levels	Automatic: 8 levels
Weight	6,8 kg	18 kg	16,5 kg	16,5 kg	18,5 kg
Dimensions l/b/h	410 x 170 x 238 mm	543 x 228 x 315 mm	543 x 228 x 315 mm	543 x 228 x 315 mm	543 x 228 x 315 mm
Torches	- Small manual torch - L.2 m D&W torch* Marking torch*	Suction torch - L. 3 m Small manual torch* D&W torch* Marking torch*	Blowing torch - L. 4 m Small manual torch* D&W torch* Marking torch*	Blowing torch - L. 4 m Small manual torch* D&W torch* Marking torch*	Blowing torch - L. 6 m Small manual torch* D&W torch* Marking torch*
Functions	Cleaning Polishing Marking	Cleaning Polishing Marking	Cleaning Polishing Marking	Cleaning Polishing Marking	Cleaning Polishing Marking